



## Zip-a-Duct 70

Zip-a-Duct 70 is a permeable, flame-retardant, Oeko-Tex 100 certified fabric. It is a strong and durable fabric; machine washable and retains its dimensions after washing (max. 0.5% shrinkage). The permeability is uniform (max. 5% variation) and achieved by thermo-fixation.

This fabric is rated for cleanrooms and associated controlled environments: Cleanliness Class 3 (ISO 14644-1 Table 1). It comes with a 10-year warranty and is supplied in 9 standard colors. All flow models, as well as shape retention options are available.

FEATURES AVAILABLE	
Washable	Yes
Warranty, years	10
Permeable	Yes
Flame Retardant	Yes

STANDARD COLORS AVAILABLE	
3000 White	
3001 Blue	
3002 Orange	
3003 Dark Gray	
3004 Black	
3005 Red	
3006 Light Gray	
3007 Green	
3008 Tan	

# DATA: Zip-a-Duct 70

## PROPERTIES

Fabric type:	Polyester	
Weight:	290 g/m <sup>2</sup> [8.55 oz/yd <sup>2</sup> ]	EN ISO 12127:1997 (ASTM D3776-96)
Thickness:	0,45 mm [0.016 inch]	EN ISO 5084:1996 (ASTM D1777-96)
Permeability:	[2 (±5%) CFM/ft <sup>2</sup> at 0.5" inwg]	EN ISO 9237:1995 (ASTM D737, Frazier)
Strength - Warp:	2700 N	EN ISO 13934-1
Strength - Weft:	900 N	EN ISO 13934-1
Shrinkage:	0,5% Max.	EN ISO 5077
Heat resistance - continuous:	from -40°C [-40°F] to +140°C [+284°F]	
Heat resistance - softening:	+240°C [+464°F]	

## CODE COMPLIANCE

Reaction to fire (European Union):	B-s1,d0	EN 13501-1
Reaction to fire (Denmark):	Yes	DS 428
Reaction to fire (France):	M1	NFP 92:507
Reaction to fire (Republic of China):	B-s1,d0,t1	GB 8624
Reaction to fire (USA):	Yes	UL 723
Reaction to fire (Canada):	Yes	ULC s102.2
Cleanrooms and associated controlled environments:	Class 3	EN ISO 14644-1

## PERFORMANCE CERTIFICATES

Safety Air Dispersion Systems:	Yes	UL 2518
--------------------------------	-----	---------

## ADDITIONAL APPROVALS

OEKO-TEX®:	Yes	OEKO-TEX® Standard 100
------------	-----	------------------------

## SHAPE RETENTION OPTIONS

All-in-One:	Yes	
Internal 360° Hoops:	Yes	

---

### Disclaimer

FabricAir® believes that all data, statements, technical information, etc., listed in this Technical Data Sheet regarding the product and the use of the product are accurate and reliable. However, the product will only be covered by FabricAir®'s guarantees or warranty if the final use for the product has been approved by FabricAir® in writing. No representative is authorized to approve the final use of the product on behalf of FabricAir®.